



Safety Data Sheet (SDS)

Product: Wet Look Tire Dressing

Manufacturer: Skyrex Inc.

427 Whitehead Ave, South River, NJ 08882

Phone: 908-245-115

1. Identification

Section	Details
Product Name	Wet Look Tire Dressing
Product Number	001
Supplier	Skyrex Inc., 427 Whitehead Ave, South River, NJ 08882
Phone	908-245-1152
Emergency Phone	CHEMTEL 1-800-255-3924
Intended Use	Tire Dressing

2. Hazard Identification

Section	Details
Classification	Combustible liquid, Category 4, Serious Eye Damage/Eye Irritation, Category 2B, Skin Corrosion/Irritation, Category 3
Signal Word	Warning
Hazard Statements	Combustible liquid and vapor. Causes eye irritation. Causes mild skin irritation.
Hazard Pictogram	

GHS Precaution Phrases	Store in cool/well-ventilated place. Keep container tightly closed. Keep away from {heat/sparks/open flames/hot surfaces}. - No smoking. Wear protective gloves/clothing and eye/face protection as specified by the manufacturer/supplier or the competent authority. Ground/bond container and receiving equipment - if the explosive is electrostatically sensitive. Use only non-sparking tools. Wash hands thoroughly after handling.
LD 50/LC 50	Ingredient CAS# 9006-65-9, Dimethicone: Not available. Ingredient CAS# 6474-47-8 OMS: 6,000 MG/KG (Oral, Rat)

3. Composition/Information on Ingredients

Section	Details	Concentration
Silicone oil (Polydimethylsiloxane)	CAS 63148-62-9,	30–50%
Odorless Mineral Spirits (OMS)	CAS 64742-47-8,	50–70%

4. First Aid Measures

Section	Details
Inhalation	Move to fresh air. Get medical attention if symptoms occur.
Skin Contact	Wash with soap and water. Remove contaminated clothing.
Eye Contact	Rinse with water for several minutes. Seek medical attention if irritation persists.
Ingestion	Do not induce vomiting. Rinse mouth and seek medical attention.

5. Fire-Fighting Measures

Section	Details
Flash Point	See physical properties
Extinguishing Media	Foam, dry chemical, CO2, water spray (if applicable)
Special Hazards	Vapors may ignite at distant sources (if combustible).
Protective Equipment	Firefighters should wear self-contained breathing apparatus.

Section	Details
Response	Use proper personal protective equipment as indicated in Section 8. Spills/Leaks: Clean up spills immediately, observing precautions in the Protective Equipment section. Sweep up, then place into a suitable container for disposal. Avoid generating dusty conditions. Provide ventilation.

6. Accidental Release Measures

7. Handling and Storage

Section	Details
Handling	Avoid contact with eyes and skin. Use with adequate ventilation. Wash thoroughly after handling material. Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Avoid contact with eyes, skin, and clothing. Avoid ingestion and inhalation.
Storage	Store in tightly closed containers away from heat and freezing.

8. Exposure Controls/Personal Protection

Section	Details
Engineering Controls	Normal ventilation adequate.
Personal Protection	Gloves, safety glasses. Respiratory protection if mist forms.

9. Physical and Chemical Properties

Section	Details
Appearance	Clear to slightly hazy blue liquid
Odor	Mild petroleum odor
Flash Point	Approx. 115 °F (43 °C) Estimate
Specific Gravity	0.80–0.85
Solubility in water	Insoluble
PH	NE

10. Stability and Reactivity

Section	Details
Stability	Stable under normal storage.
Incompatibilities	Avoid strong oxidizers and acids
Decomposition	Oxides of carbon, sulfur, silicon under fire conditions.

11. Toxicological Information

Section	Details
Exposure Routes	Skin, eyes, inhalation, ingestion
Symptoms	Irritation to skin/eyes, dizziness if inhaled, nausea if ingested
Chronic Effects	Prolonged exposure may cause dermatitis or CNS effects.
Carcinogenicity	NTP? = No, IARC Monographs? = No, OSHA Regulated? = No

12. Ecological Information

Section	Details
Impact	Surfactants used are biodegradable. Large spills may harm aquatic life.
Environmental	Terrestrial: Immobile and rarely leaches. Aquatic: Settles into sediment. Atmospheric: Eventually settles out. Will not bioconcentrate

13. Disposal Considerations

Section	Details
Method	Dispose of according to local, state, and federal regulations. Do not pour into drains. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. Transport Information

Section	Details
DOT	Combustible Liquid, N.O.S., (Mineral Spirits), PG III, 3
DOT Hazard label	Flammable Liquid
UN Number	UN1993

15. Regulatory Information

Section	Details
OSHA	Hazard communication compliant
TSCA	All components listed
EPA Hazard Categories	This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated: ☐ Yes ☒ No Acute (immediate) Health Hazard ☐ Yes ☒ No Chronic (delayed) Health Hazard ☒ Yes ☐ No Fire Hazard ☐ Yes ☒ No Sudden Release of Pressure Hazard ☐ Yes ☒ No Reactive Hazard

16. Other Information

Section	Details
Prepared By	Skyrex Inc. Compliance Team
Date of Preparation	September 19, 2025
Company Policy or Disclaimer	To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

HEALTH

1

FLAMMABILITY

1

REACTIVITY

0

PERSONAL PROTECTION

B